


Calibre 1055 & 1055B


Base Calibre 1030

- Ø28.5mm
- Train: 18.000
- Automatic
- Date & day of the week
- Sweep second
- Shock Proof



1 : 1

1055



7120



7122



7121



7123



7125



7126



7127



7128



7130



7131



7132



7134



7135



7136



7138



7139



7141



7142



7143



7145



7146



7152



8017

2 : 1



7133



7137



7140



7147



7999

1 : 1

1055 B



7155 B



7157 B



7158 B



7161 B

2 : 1



7156 B



7159 B

	7120	<i>Plate</i>		7147	<i>Set of screws for 1 watch movement</i>
	7121	<i>Center wheel with cannon pinion</i>			
1040	7122	<i>Balance cock</i>	1555	7152	<i>Bridle</i>
1040	7123	<i>Balance with Breguet hairspring, regulated</i>	1555	7155 B	<i>Star impulse finger</i>
	7125	<i>Cannon pinion, height 3,40 mm</i>		7156 B	<i>Screw for : Star impulse finger</i>
	7126	<i>Sweep-second pinion</i>		7157 B	<i>Date jumper</i>
1040	7127	<i>« Rolex Shock- resisting » device for balance, upper</i>		7158 B	<i>Day check-spring</i>
	7128	<i>Bridge for self- winding mechanism</i>		7159 B	<i>Set of screws for 1 watch movement</i>
	7130	<i>Double tothing hour wheel, height 2,46 mm</i>	1555	7161 B	<i>Calendar ring, ref. 6611</i>
1036	7131	<i>Calendar yoke</i>	1555	7999	<i>Screw for : Bridle</i>
	7132	<i>Calendar yoke spring</i>		8017	<i>Day disc</i>
	7133	<i>Screw for : Calendar yoke spring</i>			
	7134	<i>Cam with cannon</i>			
1555	7135	<i>Calendar wheel</i>			
	7136	<i>Star impulse finger</i>			
	7137	<i>Screw for : Star impulse finger</i>			
	7138	<i>Date jumper</i>			
	7139	<i>Day check-spring</i>			
	7140	<i>Screw for : Day check-spring</i>			
1555	7141	<i>Star unit</i>			
	7142	<i>Calendar ring, ref. 6511</i>			
	7143	<i>Calendar ring, ref. 6611</i>			
	7145	<i>Date disc</i>			
	7146	<i>Complete rotor</i>			