
















Calibre 1520







Ø28.50mm
Ht: 5.75mm
Train: 19.800

- Automatic
- Centre Seconds
- Shock Proof
- 26 Jewels

Base Calibre 1530

| Image | Rolex No. | Description |
|---|-----------|--|
|  | 7825 | Mainspring, strength weak |
|  | 8050 | Second wheel |
|  | 8051 | Escape wheel, 26 jewels |
|  | 8052 | Escape wheel, 17 jewels |
|  | 8053 | Balance bridge |
|  | 8055 | Balance with Breguet hairspring, timed |

| Image | Rolex No. | Description |
|---|-----------|----------------------------------|
|  | 8056-1 | Inertia-block, gilt |
| | 8056-2 | Inertia-block, nickel-plated |
|  | 8057-1 | Adjusting washer: 1/100 |
| | 8057-2 | 2/100 |
| | 8057-3 | 3/100 |
| | 8057-4 | 4/100 |
| | 8057-5 | 5/100 |
|  | 8061 | Regulator |
|  | 8062 | Stud support |
|  | 8063 | Screw for stud holder |
|  | 8064 | Automatic device upper bridge |
|  | 8065 | Shock-absorber for balance-upper |
|  | 8066 | Automatic device module |
|  | 8067 | Set of screws |

| Image | Rolex No. | Description |
|---|-----------|-------------------------------|
|  | 8069 | Mainspring, strength standard |
|  | 8073 | Balance stop spring |
|  | 8074 | Screw for balance stop spring |
|  | 8075 | Main plate |
|  | 8076 | Bush for center wheel-lower |
|  | 55051 | Screw for stud |
| | | |